


Technical Data Sheet

 <p>FP-200S</p>	TECHNICAL INFORMATION	
	Model	FP 200S
	Mass of Extinguishing material	200gr
	Activation Mode/s	Electrical 6-24VD/C, min. 0.8A for 3-4 sec. Thermally activated Thermocord at 172°C"
	Activator Type	Heating Element with 2.3Ω(ohm) Resistance
	Testing Electrical Current	Maximum 5mA
	Weight gross	1840gr Tolerance +/- 5%
	Weight net extinguishing agent	200 g
	Operational discharge time	5 - 10 seconds
	Discharge outlet	One Direction Outlet
	Dimension	150 mm x 84 mm (plus connector housing)
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
Rooms	server rooms, ceilings, floors	
Transport	car, lorry, bus, train, metro, tram	
Storage	cupboards, safes	
Large switch rooms	meter cupboards, control units	
Cabinets	electrical cabinets	
Transformers (large)	industry	



FirePro® Systems

6 Koumandarias & Spyrou Araouzou Street ,Tonia Court No.2, 6th Floor, CY-3036 Limassol,P. O. Box 54080,
CY-3720 Limassol, CYPRUS Tel: +357 25 379 999, Fax: +357 25 354 432

Web: www.firepro.info, email: mail@firepro.info

An ISO 9001:2008 & 14001:2004 registered company