


## Technical Data Sheet

 <p><b>FP-20SE</b></p>	TECHNICAL INFORMATION		
	Model	FP 20SE	
	Type	Cold	
	Activation Mode/s	Electrical 6-24VD/C, min. 0.8A for 3-4 sec.	
	Activator Type	Heating Element with 2.3Ω(ohm) Resistance	
	Testing Electrical Current	Maximum 5mA	
	Weight gross	310gr Tolerance +/- 5%	
	Weight net extinguishing agent	20 g	
	Operational discharge time	5 - 10 seconds	
	Discharge outlet	Two Direction Outlet	
	Dimension	165mm x 32mm ( incl connector housing)	
	Self activation temperature	300 °C	
	Fire class	A, B, C, F	
	APPLICATIONS		
Hardware Cabinets VDUs Sound installations Mechanical Switch boxes (medium) Transformers (medium)	computers, exchanges, projectors electrical cabinets, control, main. monitors, televisions amplifiers, mixing desks portable welder machines relay boxes, meter cupboards PFCUs		



### FirePro® Systems

6 Koumandarias & Spyrou Araouzou Street ,Tonia Court No.2, 6<sup>th</sup> Floor, CY-3036 Limassol,P. O. Box 54080,  
CY-3720 Limassol, CYPRUS Tel: +357 25 379 999, Fax: +357 25 354 432

Web: [www.firepro.info](http://www.firepro.info), email: [mail@firepro.info](mailto:mail@firepro.info)

An ISO 9001:2008 & 14001:2004 registered company