

## Technical Data Sheet

 <p><b>FP-40S</b></p>	TECHNICAL INFORMATION		
	Model	FP 40S	
	Type	Cold	
	Activation Mode/s	Electrical 6-24VD/C, min. 0.8A for 3-4 sec. Thermally activated Thermocord at 172°C"	
	Activator Type	Heating Element with 2.3Ω(ohm) Resistance	
	Testing Electrical Current	Maximum 5mA	
	Weight gross	610gr Tolerance +/- 5%	
	Weight net extinguishing agent	40 g	
	Operational discharge time	5 - 10 seconds	
	Discharge outlet	Two Direction Outlet	
	Dimension	140mm x 51mm ( incl connectors housing)	
	Self activation temperature	300 °C	
	Fire class	A, B, C, F	
	APPLICATIONS		
Hardware Cabinets Sound installations Instrumentation Switch boxes (medium) Transformers (medium)	computers, teleph. exchanges electrical cabinets amplifiers, mixing desks, speakers portable welder machines relay boxes, meter cupboards PFCUs		



### FirePro® Systems

6 Koumandarias & Spyrou Araouzou Street ,Tonia Court No.2, 6<sup>th</sup> Floor, CY-3036 Limassol,P. O. Box 54080,  
CY-3720 Limassol, CYPRUS Tel: +357 25 379 999, Fax: +357 25 354 432

Web: [www.firepro.info](http://www.firepro.info), email: [mail@firepro.info](mailto:mail@firepro.info)

An ISO 9001:2008 & 14001:2004 registered company