


Technical Data Sheet

<p>FP-500S</p> 	TECHNICAL INFORMATION		
	Model	FP-500S	
	Mass of Extinguishing material	500gr	
	Activation Mode/s	Electrical 6-24VD/C, min. 0.8A for 3-4 sec. Thermally activated Thermocord at 172°C.	
	Activator Type	Heating Element with 2.3Ω(ohm) Resistance	
	Testing Electrical Current	Maximum 5mA	
	Weight gross	3340gr Tolerance +/- 5%	
	Weight net extinguishing agent	500 g	
	Operational discharge time	5 - 10 seconds	
	Discharge outlet	One Direction Outlet	
	Dimension	260 mm x 84 mm (plus connector housing)	
	Self activation temperature	300 °C	
	Fire class	A, B, C, F	
	APPLICATIONS		
Rooms	server rooms, ceilings, floors		
Transport	car, lorry, bus, train, metro, tram		
Storage	cupboards, safes		
Large switch rooms	meter cupboards, control units		
Cabinets	electrical cabinets		
Transformers (large)	industry		



FirePro® Systems

6 Koumandarias & Spyrou Araouzou Street ,Tonia Court No.2, 6th Floor, CY-3036 Limassol,P. O. Box 54080,
CY-3720 Limassol, CYPRUS Tel: +357 25 379 999, Fax: +357 25 354 432

Web: www.firepro.info, email: mail@firepro.info