



Technical Data Sheet

TECHNICAL INFORMATION		
 <p>FP-5700S</p>	Model	FP-5700 / 5700S
	Type	Cold
	Activation Mechanism/s	thermal activation by thermocord at 172 °C electrical (6 - 36 V D/C 0.8 A in 3 - 4 sec)
	Activator Type	heating element 2.3 ohm resistance
	Testing Electrical Current	maximum 5 mA.
	Weight gross	26800 g (excl. bracket)
	Weight net extinguishing agent	5700 g
	Operational discharge time	15 - 20 seconds
	Discharge outlet	One Direction Outlet
	Discharge Length	8.0 m
 <p>FP-5700</p>	Dimension	300 mm x 300 mm x 300 mm
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
	Rooms	central control rooms, various
	Transport	shipping, train, aircraft
	Storage	store, archive
	Mechanical rooms	engine rooms, plant rooms
	Industry	various



FirePro® Systems

6 Koumandarias & Spyrou Araouzou Street ,Tonia Court No.2, 6th Floor, CY-3036 Limassol,P. O. Box 54080,
CY-3720 Limassol, CYPRUS Tel: +357 25 379 999, Fax: +357 25 354 432

Web: www.firepro.info, email: mail@firepro.info

An ISO 9001:2008 & 14001:2004 registered company